



DIN 963

ISO 2009
ГОСТ 17475-80

Винт с потайной головкой и прямым шлицем
Нержавеющая сталь A2 (AISI 304)/A4 (AISI 316)

b1	0,4	0,5	0,6	0,8	0,8	1,0	1,2	1,6	2,0	2,5	3,0	3,0
b2 - l < 125	0,96	1,2	1,5	1,65	1,93	2,2	2,5	3,0	4,0	5,0	6,0	7,0
b2 - l > 125	3,0	3,8	4,7	5,6	6,5	7,5	9,2	11,0	14,5	18,0	22,0	25,0

d1	M	M	M	M	M	M	M	M	M	M	M	M
	1,6	2	2,5	3	3,5	4	5	6	8	10	12	14

l 3	0,006												
4	0,007	0,012	0,021	0,029									
5	0,008	0,014	0,024	0,034		0,068							
6	0,009	0,015	0,027	0,038	0,055	0,075	0,121						
8	0,012	0,019	0,033	0,047		0,090	0,145	0,219					
10	0,014	0,023	0,039	0,056	0,079	0,106	0,170	0,254	0,503				
12		0,027	0,045	0,064	0,091	0,122	0,195	0,289	0,567				
14		0,031	0,051	0,073		0,137	0,219	0,325	0,630				
16		0,034	0,057	0,082	0,115	0,153	0,244	0,361	0,694	1,160			
18		0,038	0,063	0,091		0,168	0,269	0,395	0,757				
20		0,042	0,069	0,100	0,139	0,184	0,294	0,431	0,821	1,360	2,080	4,100	
22			0,075	0,108		0,199	0,318	0,466	0,884				
25		0,054	0,084	0,122	0,169	0,222	0,355	0,519	0,979	1,610	2,440	4,770	
28								0,572					
30				0,144	0,199	0,261	0,416	0,608	1,140	1,860	2,810	5,440	
35				0,156	0,229	0,299	0,476	0,696	1,300	2,110	3,170	6,110	
40				0,166		0,336	0,539	0,784	1,460	2,360	3,530	6,780	
45				0,203		0,370	0,602	0,873	1,620	2,610	3,900	7,450	
50				0,232		0,414	0,665	0,961	1,780	2,860	4,260	8,110	
55				0,275		0,452	0,728	1,049	1,940	3,110	4,620	8,780	
60				0,288		0,490	0,789	1,137	2,280	3,370	4,980	9,440	
65							0,917	1,225	2,600	3,630	5,170	10,800	
70							0,590	0,941	1,317	2,486	3,890	6,440	12,100
80							0,640	1,043	1,568	2,786	4,372	7,420	13,400
90								1,165	1,665	3,306	4,864	7,674	14,800
100								1,290	1,807	3,380	0,517		
120									2,353	4,383	6,740		
130													20,000
140													20,000
150													22,500
	1000	1000	1000	1000	1000	1000 от 25 l 500	500 от 25 l 200	200 от 35 l 100	100	100	100	50 от 100 l 25	

Вес 100 шт./кг